



Flachprofile gepresst
Méplats pressés

EN AW-6060
AlMgSi (AlMgSi0.5)
EN AW-6082
AlSi1MgMn (AlMgSi1)

Chem. Zusammensetzung DIN EN 573-3
 Composition chimique:
 Mech.Wert/ Propr. mécaniques: DIN EN 755-2
 Dimension/Dimension: DIN EN 755-5
 Stangenlänge/Longueur: ● 6 m, ○ 3 m
 Zustand/Etat: EN AW-6060 T66, EN AW-6082 T6 nach/selon DIN EN 515

mm	kg/m	EN AW-6060	EN AW-6082
8 × 2	0.04	●	
8 × 3	0.06	●	
8 × 4	0.09	●	
8 × 5	0.11	●	
10 × 2	0.05	●	
10 × 3	0.08	●	
10 × 4	0.11	●	
10 × 5	0.14	●	
10 × 6	0.16	●	
10 × 8	0.22	●	
12 × 2	0.06	●	
12 × 3	0.10	●	
12 × 4	0.13	●	
12 × 5	0.16	●	
12 × 6	0.19	●	
12 × 8	0.26	●	
12 × 10	0.32	●	
15 × 2	0.08	●	
15 × 3	0.12	●	
15 × 4	0.16	●	
15 × 5	0.20	●	
15 × 6	0.24	●	
15 × 8	0.32	●	
15 × 10	0.41	●	
18 × 3	0.15	●	
18 × 5	0.24	●	
18 × 8	0.39	●	

mm	kg/m	EN AW-6060	EN AW-6082
18 × 12	0.58	●	
20 × 2	0.11	●	
20 × 3	0.16	●	
20 × 4	0.22	●	
20 × 5	0.27	●	
20 × 6	0.32	●	
20 × 8	0.43	●	
20 × 10	0.54	●	
20 × 12	0.65	●	
20 × 15	0.81	●	
25 × 2	0.14	●	
25 × 3	0.20	●	
25 × 4	0.27	●	
25 × 5	0.34	●	
25 × 6	0.41	●	
25 × 8	0.54	●	
25 × 10	0.68	●	
25 × 12	0.81	●	
25 × 15	1.01	●	
25 × 20	1.35	●	
30 × 2	0.16	●	
30 × 3	0.24	●	
30 × 4	0.32	●	
30 × 5	0.41	●	
30 × 6	0.49	●	
30 × 8	0.65	●	
30 × 10	0.81	●	

Fortsetzung siehe Seite 3.11/suite voir page 3.11



mm	kg/m	EN AW-6060	EN AW-6082
30 × 12	0.97	●	
30 × 15	1.22	●	
30 × 20	1.62	●	
30 × 25	2.03	●	
35 × 2	0.19	●	
35 × 3	0.28	●	
35 × 4	0.38	●	
35 × 5	0.47	●	
35 × 6	0.57	●	
35 × 8	0.76	●	
35 × 10	0.95	●	
35 × 12	1.13	●	
35 × 15	1.42	●	
35 × 20	1.89	●	
35 × 25	2.36	●	
40 × 2	0.22	●	
40 × 3	0.32	●	
40 × 4	0.43	●	
40 × 5	0.54	●	
40 × 6	0.65	●	
40 × 8	0.86	●	
40 × 10	1.08	●	
40 × 12	1.30	●	
40 × 15	1.62	●	
40 × 20	2.16	●	
40 × 25	2.70	●	
40 × 30	3.24	●	
45 × 4	0.49	●	
45 × 5	0.61	●	
45 × 6	0.73	●	
45 × 8	0.97	●	
45 × 10	1.22	●	
45 × 20	2.43	●	
50 × 2	0.27	●	
50 × 3	0.41	●	
50 × 4	0.54	●	
50 × 5	0.68	●	
50 × 6	0.81	●	
50 × 8	1.08	●	
50 × 10	1.35	●	
50 × 12	1.62	●	
50 × 15	2.03		●
50 × 20	2.70		●

mm	kg/m	EN AW-6060	EN AW-6082
50 × 25	3.38		●
50 × 30	4.05		●
50 × 40	5.40		●
60 × 3	0.49	●	
60 × 4	0.65	●	
60 × 5	0.81	●	
60 × 6	0.97	●	
60 × 8	1.30	●	
60 × 10	1.62	●	
60 × 12	1.94	●	
60 × 15	2.43		●
60 × 20	3.24		●
60 × 25	4.05	●	
60 × 30	4.86		●
60 × 35	5.67		●
60 × 40	6.48		●
70 × 3	0.57	●	
70 × 4	0.76	●	
70 × 5	0.95	●	
70 × 6	1.13	●	
70 × 8	1.51	●	
70 × 10	1.89	●	
70 × 12	2.27	●	
70 × 15	2.84	●	
70 × 20	3.78		●
70 × 25	4.73		●
70 × 30	5.67		●
70 × 40	7.56		●
80 × 3	0.65	●	
80 × 4	0.86	●	
80 × 5	1.08	●	
80 × 6	1.30	●	
80 × 8	1.73	●	
80 × 10	2.16	●	
80 × 12	2.59	●	
80 × 15	3.24		●
80 × 20	4.32		●
80 × 25	5.40		●
80 × 30	6.48		●
80 × 40	8.64		●
80 × 50	10.80		●
80 × 60	12.96		○
90 × 8	1.94	●	

Fortsetzung siehe Seite 3.12/suite voir page 3.12



mm		kg/m	EN AW-6060	EN AW-6082
100	× 3	0.81	●	
100	× 4	1.08	●	
100	× 5	1.35	●	
100	× 6	1.62	●	
100	× 8	2.16	●	
100	× 10	2.70	●	
100	× 12	3.24	●	
100	× 15	4.05		●
100	× 20	5.40		●
100	× 25	6.75		●
100	× 30	8.10		●
100	× 40	10.80		●
100	× 50	13.50		●
100	× 60	16.20		○
120	× 4	1.30	●	
120	× 5	1.62	●	
120	× 6	1.94	●	
120	× 8	2.59	●	
120	× 10	3.24	●	
120	× 12	3.89	●	
120	× 15	4.86		●
120	× 20	6.48		●
120	× 30	9.72		●
120	× 50	16.20		○
120	× 60	19.44		○
150	× 10	4.05	●	
150	× 12	4.86	●	
150	× 15	6.08		●
150	× 20	8.10		●
150	× 30	12.15		○
150	× 40	16.20		○
150	× 50	20.25		○
200	× 10	5.40	●	
200	× 12	6.48	●	
200	× 15	8.10	●	
200	× 20	10.80		●
250	× 10	6.75	●	

Flachprofile EN AW-2030 (AlCu4PbMg) kurzfristig ab Werkslager lieferbar.

Méplats EN AW-2030 (AlCu4PbMg) disponibles rapidement du stock usine.