



Winkelprofile gepresst
Equerres pressées

EN AW-6060
AlMgSi (AlMgSi0.5)
EN AW-6082
AlSi1MgMn (AlMgSi1)

Chem. Zusammensetzung DIN EN 573-3
 Composition chimique:
 Mech.Wert/Prop. mécaniques: DIN EN 755-2
 Dimension/Dimension: DIN EN 755-9
 Stangenlänge/Longueur: ca./env. 6 m
 Zustand/Etat: EN AW-6060 T66, EN AW-6082 T6, nach/selon DIN EN 515

mm				kg/m	EN AW-6060	EN AW-6082
10	×	10	×	2	0.10	●
12	×	12	×	2	0.12	●
15	×	10	×	2	0.12	●
15	×	15	×	2	0.15	●
15	×	15	×	3	0.22	●
20	×	10	×	2	0.15	●
20	×	10	×	3	0.22	●
20	×	15	×	2	0.18	●
20	×	15	×	3	0.26	●
20	×	20	×	2	0.21	●
20	×	20	×	3	0.30	●
20	×	20	×	4	0.39	●
25	×	10	×	2	0.18	●
25	×	15	×	2	0.21	●
25	×	15	×	3	0.30	●
25	×	20	×	2	0.23	●
25	×	20	×	3	0.34	●
25	×	25	×	2	0.26	●
25	×	25	×	3	0.38	●
25	×	25	×	4	0.50	●
30	×	10	×	2	0.21	●
30	×	10	×	3	0.30	●
30	×	15	×	2	0.23	●
30	×	15	×	3	0.34	●
30	×	15	×	4	0.44	●
30	×	20	×	2	0.26	●
30	×	20	×	3	0.38	●

mm				kg/m	EN AW-6060	EN AW-6082
30	×	20	×	4	0.50	●
30	×	25	×	2	0.29	●
30	×	25	×	3	0.42	●
30	×	30	×	2	0.31	●
30	×	30	×	3	0.46	●
30	×	30	×	4	0.60	●
30	×	30	×	5	0.74	●
35	×	15	×	3	0.38	●
35	×	20	×	4	0.55	●
35	×	25	×	2	0.31	●
35	×	35	×	3	0.54	●
35	×	35	×	4	0.71	●
40	×	10	×	3	0.38	●
40	×	15	×	3	0.42	●
40	×	20	×	2	0.31	●
40	×	20	×	3	0.46	●
40	×	20	×	4	0.60	●
40	×	25	×	2.5	0.42	●
40	×	25	×	3	0.50	●
40	×	25	×	4	0.66	●
40	×	30	×	3	0.54	●
40	×	30	×	4	0.71	●
40	×	40	×	2	0.42	●
40	×	40	×	3	0.62	●
40	×	40	×	4	0.82	●
40	×	40	×	5	1.01	●
40	×	40	×	6	1.20	●

Fortsetzung siehe Seite 3.14/suite voir page 3.14



mm				kg/m	EN AW-6060	EN AW-6082
45	×	30	×	4	0.77	●
45	×	45	×	4	0.93	●
45	×	45	×	5	1.15	●
50	×	20	×	4	0.71	●
50	×	25	×	3	0.58	●
50	×	25	×	4	0.77	●
50	×	30	×	3	0.62	●
50	×	30	×	4	0.82	●
50	×	50	×	3	0.79	●
50	×	50	×	4	1.04	●
50	×	50	×	5	1.28	●
50	×	50	×	8	1.99	●
60	×	30	×	3	0.70	●
60	×	40	×	3	0.79	●
60	×	30	×	4	0.93	●
60	×	40	×	4	1.04	●
60	×	40	×	5	1.28	●
60	×	40	×	6	1.52	●
60	×	50	×	8	2.20	●
60	×	60	×	4	1.25	●
60	×	60	×	5	1.55	●
60	×	60	×	6	1.85	●
60	×	60	×	10	2.97	●
64	×	40	×	4	1.08	●
70	×	30	×	3	0.79	●
70	×	50	×	4	1.25	●
70	×	50	×	8	2.42	●
70	×	70	×	5	1.82	●
80	×	20	×	2	0.53	●
80	×	30	×	3	0.87	●
80	×	40	×	4	1.25	●
80	×	40	×	5	1.55	●
80	×	50	×	6	2.01	●
80	×	50	×	6.4	2.14	●
80	×	80	×	5	2.09	●
80	×	80	×	6.5	2.69	●
80	×	80	×	8	3.28	●
90	×	60	×	4	1.58	●
90	×	60	×	6	2.33	●
90	×	90	×	6	2.82	●
90	×	90	×	9	4.16	●
100	×	50	×	9	3.43	●
100	×	64	×	6.5	2.76	●

mm				kg/m	EN AW-6060	EN AW-6082
100	×	100	×	4	2.12	●
100	×	100	×	8	4.15	●
105	×	40	×	4	1.52	●
120	×	80	×	8	4.15	●
120	×	120	×	11	6.80	●