



U-Profile gepresst
Profilés U pressés

EN AW-6060
AlMgSi (AlMgSi0.5)
EN AW-6082
AlSi1MgMn (AlMgSi1)

Chem. Zusammensetzung: DIN EN 573-3
 Composition chimique:
 Mech.Wert/Prop. mécaniques: DIN EN 755-2
 Dimension/Dimension: DIN EN 755-9
 Stangenlänge/Longueur: ca./env. 6 m
 Zustand/Etat: EN AW-6060 T66, EN AW-6082 T6, nach/selon DIN EN 515

a	b	c	kg/m	EN AW-6060	EN AW-6082
10 × 10 × 1	0.08	●			
10 × 10 × 2	0.14	●			
12 × 15 × 2	0.21	●			
13 × 18 × 2	0.24	●			
15 × 12 × 2	0.19	●			
15 × 15 × 2	0.22	●			
20 × 10 × 2	0.19	●			
20 × 15 × 2	0.25	●			
20 × 20 × 2	0.30	●			
20 × 20 × 3	0.44	●			
20 × 25 × 4	0.67	●			
22 × 15 × 3	0.37	●			
25 × 15 × 2	0.28	●			
25 × 15 × 3	0.40	●			
25 × 25 × 2	0.38	●			
25 × 25 × 3	0.56	●			
30 × 15 × 3	0.44	●			
30 × 20 × 2	0.36	●			
30 × 20 × 3	0.52	●			
30 × 25 × 4	0.78	●			
30 × 30 × 2	0.46	●			
30 × 30 × 3	0.68	●			
35 × 25 × 2.5	0.54	●			
35 × 35 × 3	0.80	●			
40 × 20 × 2	0.41	●			
40 × 20 × 4	0.78	●			
40 × 25 × 3	0.68	●			

a	b	c	kg/m	EN AW-6060	EN AW-6082
40 × 25 × 4	0.89	●			
40 × 30 × 4	0.99	●			
40 × 40 × 3	0.92	●			
40 × 40 × 4	1.21	●			
50 × 25 × 2.5	0.64	●			
50 × 25 × 4	0.99	●			
50 × 30 × 3	0.84	●			
50 × 30 × 4	1.10	●			
50 × 30 × 5	1.35	●			
50 × 40 × 4	1.32	●			
50 × 50 × 4	1.53	●			
50 × 50 × 5	1.89	●			
60 × 30 × 4	1.21	●			
80 × 30 × 5	1.76	●			
80 × 40 × 4	1.64	●			
90 × 50 × 8/7	3.66		●		
100 × 50 × 8/6.5	3.71		●		
108 × 60 × 8/5	3.92		●		
120 × 65 × 10/8	5.83		●		