



Vierkantrohre gepresst Tubes carrés pressés

EN AW-6060 AlMgSi (AlMgSi0.5)

Chem. Zusammensetzung: DIN EN 573-3
 Composition chimique:
 Mech. Wert/Prop. mécaniques: DIN EN 755-2
 Dimension/Dimension: DIN EN 755-9
 Stangenlänge/Longueur: 6 m
 Zustand/Etat: T6, nach/selon DIN EN 515

mm				kg/m	EN AW-6060	
15	×	15	×	1	0.15	●
15	×	15	×	1.5	0.22	●
15	×	15	×	2	0.28	●
20	×	20	×	1.5	0.30	●
20	×	20	×	2	0.39	●
20	×	20	×	3	0.55	●
25	×	25	×	1.5	0.38	●
25	×	25	×	2	0.50	●
25	×	25	×	3	0.71	●
30	×	30	×	2	0.60	●
30	×	30	×	3	0.87	●
34	×	34	×	2	0.69	●
34	×	34	×	3	1.00	●
35	×	35	×	2	0.71	●
35	×	35	×	3	1.04	●
40	×	40	×	2	0.82	●
40	×	40	×	2.5	1.01	●
40	×	40	×	3	1.20	●
40	×	40	×	4	1.56	●
45	×	45	×	2	0.93	●
50	×	50	×	2	1.04	●
50	×	50	×	2.5	1.28	●
50	×	50	×	3	1.52	●
50	×	50	×	4	1.99	●
50	×	50	×	5	2.43	●
60	×	60	×	2	1.25	●
60	×	60	×	3	1.85	●
60	×	60	×	4	2.42	●
70	×	70	×	2	1.47	●

mm				kg/m	EN AW-6060	
70	×	70	×	4	2.85	●
80	×	80	×	2	1.68	●
80	×	80	×	3	2.49	●
80	×	80	×	4	3.28	●
80	×	80	×	5	4.05	●
80	×	80	×	6	4.80	●
100	×	100	×	2	2.12	●
100	×	100	×	3	3.14	●
100	×	100	×	4	4.15	●
100	×	100	×	5	5.13	●