



## Vierkantrohre gepresst Tubes carrés pressés

## EN AW-6060 AlMgSi (AlMgSi0.5)

Chem. Zusammensetzung      DIN EN 573-3  
 Composition chimique:  
 Mech.Wert/Prop. mécaniques:    DIN EN 755-2  
 Dimension/Dimension:            DIN EN 755-9  
 Stangenlänge/Longueur:        6 m  
 Zustand/Etat:                      T6, nach/selon DIN EN 515

mm	kg/m	EN AW-6060
15 x 15 x 1	0.15	●
15 x 15 x 1.5	0.22	●
15 x 15 x 2	0.28	●
20 x 20 x 1.5	0.30	●
20 x 20 x 2	0.39	●
20 x 20 x 3	0.55	●
25 x 25 x 1.5	0.38	●
25 x 25 x 2	0.50	●
25 x 25 x 3	0.71	●
30 x 30 x 2	0.60	●
30 x 30 x 3	0.87	●
34 x 34 x 2	0.69	●
34 x 34 x 3	1.00	●
35 x 35 x 2	0.71	●
35 x 35 x 3	1.04	●
40 x 40 x 2	0.82	●
40 x 40 x 2.5	1.01	●
40 x 40 x 3	1.20	●
40 x 40 x 4	1.56	●
45 x 45 x 2	0.93	●
50 x 50 x 2	1.04	●
50 x 50 x 2.5	1.28	●
50 x 50 x 3	1.52	●
50 x 50 x 4	1.99	●
50 x 50 x 5	2.43	●
60 x 60 x 2	1.25	●
60 x 60 x 3	1.85	●
60 x 60 x 4	2.42	●
70 x 70 x 2	1.47	●

mm	kg/m	EN AW-6060
70 x 70 x 4	2.85	●
80 x 80 x 2	1.68	●
80 x 80 x 3	2.49	●
80 x 80 x 4	3.28	●
80 x 80 x 5	4.05	●
80 x 80 x 6	4.80	●
100 x 100 x 2	2.12	●
100 x 100 x 3	3.14	●
100 x 100 x 4	4.15	●
100 x 100 x 5	5.13	●