



**Flachprofile gepresst**  
**Méplats pressés**

**EN AW-6060**  
**AlMgSi (AlMgSi0.5)**  
**EN AW-6082**  
**AlSi1MgMn (AlMgSi1)**

Chem. Zusammensetzung      DIN EN 573-3  
 Composition chimique:  
 Mech.Wert/ Propr. mécaniques: DIN EN 755-2  
 Dimension/Dimension:      DIN EN 755-5  
 Stangenlänge/Longueur:      ● 6 m, ○ 3 m  
 Zustand/Etat:                  EN AW-6060 T66, EN AW-6082 T6 nach/selon DIN EN 515

mm	kg/m	EN AW-6060	EN AW-6082
8 x 2	0.04	●	
8 x 3	0.06	●	
8 x 4	0.09	●	
8 x 5	0.11	●	
10 x 2	0.05	●	
10 x 3	0.08	●	
10 x 4	0.11	●	
10 x 5	0.14	●	
10 x 6	0.16	●	
10 x 8	0.22	●	
12 x 2	0.06	●	
12 x 3	0.10	●	
12 x 4	0.13	●	
12 x 5	0.16	●	
12 x 6	0.19	●	
12 x 8	0.26	●	
12 x 10	0.32	●	
15 x 2	0.08	●	
15 x 3	0.12	●	
15 x 4	0.16	●	
15 x 5	0.20	●	
15 x 6	0.24	●	
15 x 8	0.32	●	
15 x 10	0.41	●	
18 x 3	0.15	●	
18 x 5	0.24	●	
18 x 8	0.39	●	

mm	kg/m	EN AW-6060	EN AW-6082
18 x 12	0.58	●	
20 x 2	0.11	●	
20 x 3	0.16	●	
20 x 4	0.22	●	
20 x 5	0.27	●	
20 x 6	0.32	●	
20 x 8	0.43	●	
20 x 10	0.54	●	
20 x 12	0.65	●	
20 x 15	0.81	●	
25 x 2	0.14	●	
25 x 3	0.20	●	
25 x 4	0.27	●	
25 x 5	0.34	●	
25 x 6	0.41	●	
25 x 8	0.54	●	
25 x 10	0.68	●	
25 x 12	0.81	●	
25 x 15	1.01	●	
25 x 20	1.35	●	
30 x 2	0.16	●	
30 x 3	0.24	●	
30 x 4	0.32	●	
30 x 5	0.41	●	
30 x 6	0.49	●	
30 x 8	0.65	●	
30 x 10	0.81	●	

Fortsetzung siehe Seite 3.11/suite voir page 3.11



mm	kg/m	EN AW-6060	EN AW-6082
30 x 12	0.97	●	
30 x 15	1.22	●	
30 x 20	1.62	●	
30 x 25	2.03	●	
35 x 2	0.19	●	
35 x 3	0.28	●	
35 x 4	0.38	●	
35 x 5	0.47	●	
35 x 6	0.57	●	
35 x 8	0.76	●	
35 x 10	0.95	●	
35 x 12	1.13	●	
35 x 15	1.42	●	
35 x 20	1.89	●	
35 x 25	2.36	●	
40 x 2	0.22	●	
40 x 3	0.32	●	
40 x 4	0.43	●	
40 x 5	0.54	●	
40 x 6	0.65	●	
40 x 8	0.86	●	
40 x 10	1.08	●	
40 x 12	1.30	●	
40 x 15	1.62	●	
40 x 20	2.16	●	
40 x 25	2.70	●	
40 x 30	3.24	●	
45 x 4	0.49	●	
45 x 5	0.61	●	
45 x 6	0.73	●	
45 x 8	0.97	●	
45 x 10	1.22	●	
45 x 20	2.43	●	
50 x 2	0.27	●	
50 x 3	0.41	●	
50 x 4	0.54	●	
50 x 5	0.68	●	
50 x 6	0.81	●	
50 x 8	1.08	●	
50 x 10	1.35	●	
50 x 12	1.62	●	
50 x 15	2.03		●
50 x 20	2.70		●

mm	kg/m	EN AW-6060	EN AW-6082
50 x 25	3.38		●
50 x 30	4.05		●
50 x 40	5.40		●
60 x 3	0.49	●	
60 x 4	0.65	●	
60 x 5	0.81	●	
60 x 6	0.97	●	
60 x 8	1.30	●	
60 x 10	1.62	●	
60 x 12	1.94	●	
60 x 15	2.43		●
60 x 20	3.24		●
60 x 25	4.05	●	
60 x 30	4.86		●
60 x 35	5.67		●
60 x 40	6.48		●
70 x 3	0.57	●	
70 x 4	0.76	●	
70 x 5	0.95	●	
70 x 6	1.13	●	
70 x 8	1.51	●	
70 x 10	1.89	●	
70 x 12	2.27	●	
70 x 15	2.84	●	
70 x 20	3.78		●
70 x 25	4.73		●
70 x 30	5.67		●
70 x 40	7.56		●
80 x 3	0.65	●	
80 x 4	0.86	●	
80 x 5	1.08	●	
80 x 6	1.30	●	
80 x 8	1.73	●	
80 x 10	2.16	●	
80 x 12	2.59	●	
80 x 15	3.24		●
80 x 20	4.32		●
80 x 25	5.40		●
80 x 30	6.48		●
80 x 40	8.64		●
80 x 50	10.80		●
80 x 60	12.96		○
90 x 8	1.94	●	

Fortsetzung siehe Seite 3.12/suite voir page 3.12



mm			kg/m	EN AW-6060	EN AW-6082
100	x	3	0.81	●	
100	x	4	1.08	●	
100	x	5	1.35	●	
100	x	6	1.62	●	
100	x	8	2.16	●	
100	x	10	2.70	●	
100	x	12	3.24	●	
100	x	15	4.05		●
100	x	20	5.40		●
100	x	25	6.75		●
100	x	30	8.10		●
100	x	40	10.80		●
100	x	50	13.50		●
100	x	60	16.20		○
120	x	4	1.30	●	
120	x	5	1.62	●	
120	x	6	1.94	●	
120	x	8	2.59	●	
120	x	10	3.24	●	
120	x	12	3.89	●	
120	x	15	4.86		●
120	x	20	6.48		●
120	x	30	9.72		●
120	x	50	16.20		○
120	x	60	19.44		○
150	x	10	4.05	●	
150	x	12	4.86	●	
150	x	15	6.08		●
150	x	20	8.10		●
150	x	30	12.15		○
150	x	40	16.20		○
150	x	50	20.25		○
200	x	10	5.40	●	
200	x	12	6.48	●	
200	x	15	8.10	●	
200	x	20	10.80		●
250	x	10	6.75	●	

Flachprofile EN AW-2030 (AlCu4PbMg) kurzfristig ab Werkslager lieferbar.

Méplats EN AW-2030 (AlCu4PbMg) disponibles rapidement du stock usine.