



U-Profile gepresst
Profils U pressés

CW614N
CW620N
CW623N

CuZn39Pb3
CuZn41Pb1Al
CuZn43Pb2

Norm/Norme:

DIN EN 12167

Zustand

gepresst, ohne vorgeschriebene Festigkeitswerte

Etat:

pressé, caractéristiques mécaniques non définies

Stangenlänge/Longueur:

5 m

| a | | mm | | c | kg/m | CuZn39Pb3 CuZn41Pb1Al CuZn43Pb2 |
|----|---|----|---|---|------|---------------------------------------|
| | | b | | | | |
| 6 | X | 6 | X | 1 | 0.14 | • |
| 8 | X | 8 | X | 1 | 0.19 | • |
| 10 | X | 10 | X | 1 | 0.24 | • |
| 10 | x | 10 | x | 2 | 0.44 | • |
| 12 | x | 12 | x | 1 | 0.29 | • |
| 12 | x | 12 | x | 2 | 0.54 | • |
| 12 | x | 15 | x | 2 | 0.65 | • |
| 15 | x | 12 | x | 2 | 0.65 | • |
| 15 | x | 15 | x | 2 | 0.70 | • |
| 16 | x | 30 | x | 3 | 1.07 | • |
| 20 | x | 10 | x | 2 | 0.61 | • |
| 20 | X | 20 | x | 2 | 0.95 | • |
| 20 | X | 20 | X | 3 | 1.38 | • |
| 25 | X | 25 | X | 2 | 1.21 | • |
| 25 | X | 25 | X | 3 | 1.76 | • |
| 30 | X | 30 | X | 3 | 2.10 | • |