

Intensités admissibles à une température ambiante de 20 °

MAXIFLEX		Echauffement du conducteur							poids barre
		80°C	70°C	60°C	50°C	40°C	30°C	20°C	
Type	Section	Intensités admissibles							
8x 6 x0,5	24	210	196	182	166	143	128	104	0.62
3x 9 x 0,8	21.6	170	158	147	134	120	104	85	0.43
6x 9 x 0,8	43.2	310	290	269	245	220	190	155	0.81
9x 9 x0,8	64.8	336	314	291	265	237	206	168	1.19
3x13x0,5	19.5	212	198	184	167	150	130	106	0.45
6x13x0,5	39	320	300	277	253	226	196	160	0.79
2x15,5x0,8	24.8	270	252	234	212	191	165	135	0.58
4x15,5x0,8	51.2	405	380	350	320	286	248	202	1.02
6x15,5x0,8	76.8	510	476	440	402	360	318	260	1.5
10x 1,5x0,8	124	575	538	498	455	407	352	287	2.5
2x20x1,0	40	348	326	300	275	246	214	175	1.05
3x20x1,0	60	457	428	395	360	323	280	228	1.42
4x20x1,0	80	510	476	440	402	360	312	255	1.78
5x20x1,0	100	532	498	460	420	376	326	266	2.15
6x20x1,0	120	585	546	506	462	413	358	292	2.52
10x20x1,0	200	815	762	706	645	576	500	407	3
2x24x1,0	48	480	450	416	380	340	295	240	1.24
3x24x1,0	72	523	490	453	413	370	320	261	1.68
4x24x1,0	96	590	550	510	465	416	360	294	2.12
5x24x1,0	120	650	608	563	514	460	398	325	2.55
6x24x1,0	144	716	670	620	566	506	438	358	2.99
8x24x1,0	192	858	802	743	678	606	525	428	3.87
10x24x1,0	240	1015	948	877	800	716	592	483	4.75
2x32x1,0	64	515	480	445	406	363	315	257	1.62
3x32x1,0	96	608	570	525	480	430	372	303	2.2
4x32x1,0	128	693	648	600	548	490	425	347	2.78
5x32x1,0	160	810	758	702	640	573	496	405	3.36
6x32x1,0	192	905	846	783	715	640	555	453	3.94
8x32x1,0	256	1090	1018	943	860	770	667	545	5.1
10x32x1,0	320	1312	1230	1140	1040	930	805	657	6.27
2x40x1,0	80	575	538	500	455	406	352	287	1.99
3x40x1,0	120	660	617	570	522	466	405	330	2.72
4x40x1,0	160	777	727	673	615	550	476	388	3.44
5x40x1,0	200	960	900	832	760	680	590	481	4.16
6x40x1,0	240	1090	1018	943	860	770	667	544	4.89
8x40x1,0	320	1315	1230	1140	1040	930	805	657	6.33
10x40x1,0	400	1495	1400	1295	1181	1055	915	747	7.78
3x50x1,0	150	750	700	650	592	530	460	375	3.37
4x50x1,0	200	920	860	795	727	650	563	460	4.27
5x50x1,0	250	1175	1100	1016	930	830	718	586	5.17
6x50x1,0	300	1310	1225	1135	1035	925	802	654	6.07
8x50x1,0	400	1490	1393	1290	1175	1050	912	744	7.87
10x50x1,0	500	1763	1650	1525	1395	1245	1080	882	9.68
3x63x1,0	189	853	798	740	675	603	522	428	4.21
4x63x1,0	252	1080	1010	935	855	763	661	540	5.34
5x63x1,0	315	1300	1220	1125	1030	920	797	650	6.48
6x63x1,0	378	1537	1437	1330	1215	1085	941	768	7.61
8x63x1,0	504	1763	1650	1525	1395	1245	1080	882	9.88
10x63x1,0	630	2030	1895	1755	1600	1435	1240	1012	12.14
3x80x1,0	240	1045	980	906	827	740	640	522	5.32
4x80x1,0	320	1280	1200	1110	1015	906	785	640	6.75
5x80x1,0	400	1485	1390	1285	1175	1050	910	743	8.19
6x80x1,0	480	1740	1627	1505	1375	1230	1065	870	9.62
8x80x1,0	640	2030	1895	1755	1600	1430	1240	1012	12.49
10x80x1,0	800	2245	2100	1945	1775	1585	1375	1122	15.37
4x100x1,0	400	1546	1446	1340	1225	1093	947	773	8.41
5x100x1,0	500	1750	1635	1515	1385	1235	1070	873	10.2
6x100x1,0	600	1970	1843	1705	1550	1393	1205	983	11.99
8x100x1,0	800	2295	2147	1990	1815	1625	1405	1147	15.57
10x100x1,0	1000	2510	2350	2170	1985	1775	1535	1253	19.16
12x100x1,0	1200	2675	2500	2315	2115	1890	1636	1335	22.74

Sous réserve des erreurs et changements techniques

This document was created with Win2PDF available at <http://www.win2pdf.com>.
The unregistered version of Win2PDF is for evaluation or non-commercial use only.
This page will not be added after purchasing Win2PDF.